
First floor to be limited to a maximum of 60 occupants due to existing door swing direction at base of stairs on escape route.

Ground Floor to be limited to a maximum of 60 occupants due to doors D0.09/01 and D0.02/01 opening direction on escape route.





Street Parish Rooms

Proposed First Floor GA revision date 11.10.19 22.10.19 A - Preparation for Public Consultation B - BC issue for comment scale 1:50 @ A1 C - maximum occupation note added 31.10.19 1228/121 revE 07.11.19 D - Replacement of male WC door E - Minor amendments to text 18.11.19

Proposed Key

Proposed Works

First Floor

Structural Element Above

Area of sreed fill / ramped area

23. Block up former kitchen extract vent hole. Demolition item 14, drawing 1228/110

24. Disabled refuge to be located in front of lift doors. Size required 900x1400mm. 25. Lift lobby floor to be cut back as required. joist sizes and directions to be specified

28. Allow provisional sum for new toilet seats to be installed to both WCs on first floor

30. Existing internal window to be infilled with dense blockwork. One skin to either side. Blockwork to be tied into existing wall cheeks with wall ties as required. 12.5mm plaster board on dot and dab to line through with existing once skimmed. Mesh to be applied across joint with existing prior to skim coat.

29. Replace 1 no. low level obscured window pane to match other. See window

31. New studwork wall to enclose lift shaft. Studwork wall to be 90mm studs with rockwool insulation between. 2no. layer of 12.5mm plasterboard to either side to

26. Lift shaft to be ventilated by at high level. Fire damper required.

27. New door D1.06/01 to be installed

provide 60 minute wall.

Note: